# UNIVERSAL DATA SHEET

| Item Code | Item Name |
|---|---|
| 3814B010 | EOS 7D EF28-135mm IS Kit |

Product Photo:

| Item Dimensions | W | H | D | WEIGHT |
|---|---|---|---|---|
| | 5.8 in | 4.4 in | 2.9 in | 28.92 oz. |

| Case Dimensions | Quantity | L | W | H | CUBIC FT. | WEIGHT |
|---|---|---|---|---|---|---|
| Unit Carton | 1 | 9.803 in | 7.205 in | 5.551 in | 0.227 c.ft. | 5.520 lb |
| Inner Carton | NA | | | | | |
| Master Carton | 6 | 17.362 in | 15.039 in | 11.339 in | 1.713 c.ft. | 35.053 lb |

| Item Description | Kit Includes |
|---|---|
| • 18.0 Megapixel CMOS Sensor and Dual DIGIC 4 Image Processors for high image quality and speed. | EOS 7D BODY |
| • ISO 100-6400 (expandable to 12,800) for shooting from bright to dim light. | EF 28-135mm f/3.5-5.6 IS USM |
| • 8.0 fps continuous shooting up to 130†/* JPEG Large/Fine and 25†/* RAW images. | EYECUP EG |
| †Figure based on updated firmware, ISO 100, Standard Picture Style and with UDMA 7 CF | CAMERA COVER R-F-3 |
| memory cards. Note: UDMA 7 CF memory card read/write speeds are not fully supported with the | WIDE STRAP EW-EOS7D |
| EOS 7D Digital SLR camera, if using UDMA 7 memory cards, the read/write speeds will be | BATTERY CHARGER LC-E6 |
| equivalent to UDMA 6. | BATTERY PACK LP-E6 |
| • Advanced movie mode with manual exposure control, manual audio adjustment (64 levels)*, | STEREO AV CABLE AVC-DC400ST |
| and selectable frame rates: 1920x1080 (Full HD): 30p(29.97)/24p(23.976)/25p, | INTERFACE CABLE IFC-200U |
| 1280x720(HD): 60p(59.94)/50p, 640x480(SD): 60p(59.94)/50p. | EOS DIGITAL SOLUTION DISK |
| • Intelligent Viewfinder with 100% field of view, wide viewing angle of 29.4°, high magnification of 1.0, | CAMERA INSTRUCTION BOOK (E/S) |
| intelligent viewfinder with glass pentaprism and superimposed LCD display in viewfinder supports | SOFTWARE INSTRUCTION BOOK CD |
| various shooting styles. | POCKET GUIDE (E/S) |
| • 19 point, all cross-type AF system equipped with dual diagonal cross-type sensors | CD-ROM GUIDE |
| in center at f/2.8 and f/5.6 and AF area selection modes to match various shooting situations. | ACC PROMOTIONAL CD |
| • iFCL Metering with 63 zone dual—layer metering sensor that utilizes AF and color information | BARCODE LEAFLET OF DOCUMENT PACK NO. |
| for optimizing exposure and image quality. | LEAFLET OF DIGITAL LEARNING CENTER WEBSITE |
| • Magnesium body with shutter durability up to 150,000 cycles and exclusive dust and weather resistance. | CAMERA WARRANTY CARD (NA) |
| • Compatible with the optional GPS Receiver GP-E2* to record the time and location information of images. | |
| *Firmware upgrade (Version 2.0.X) is required. | |
| | |
| | |
| | |

| UPC Code | Master Carton Code (SCC14) | Inner Carton Code (If Any) |
|---|---|---|
| 0 13803 11753 0 | 10 0 13803 11753 7 | |

013803117530

UPC BAR CODE

10013803117537

MASTER CARTON BAR CODE

| Warranty | | Country of Origin | Batt. Req? | Included Battery | Batt. Qty | UL # |
|---|---|---|---|---|---|---|
| LENGTH | TYPE | Japan | Yes | LP-E6 | 1 | |
| 1 Year | LTD. | | | | | |

Product Number: 0345B002

# EF 70-300mm f/4-5.6 IS USM Lens

The EF 70-300mm f/4-5.6 IS USM telephoto zoom lens has been developed to meet the high-performance standards that today's photographer demands. Improved Image Stabilizer Technology provides up to three stops of "shake" correction, and the "Mode 2" option stabilizes images while panning with a moving subject. Compared to the original Canon EF 75-300mm IS zoom lens, this telephoto lens has faster autofocus, and overall the lens is lighter and has a smaller diameter than the original. The zoom ring can be locked at the 70mm position, making this powerful lens easy to transport, too.

## Specifications

| | |
|---|---|
| Lens | |
| Focal Length & Maximum Aperture | 70-300mm f/4-5.6 |
| Lens Construction | 15 elements in 10 groups |
| Diagonal Angle of View | 34° - 8° 15' (with full-frame camera) |
| Focus Adjustment | Front-focusing method with helicoid ring drive |
| Closest Focusing Distance | 4.9 ft. / 1.5m |
| Zoom System | 6-group helical zoom (rotational angle: 84°) |
| Filter Size | 58mm |
| Max. Diameter x Length, Weight | 3.0 in. x 5.6 in., 22.2 oz. / 76.5mm x 142.8mm, 630g (lens only) |

Product Number: 300 DG

# Black Digital Gadget Bag

If you love your digital SLR cameras and lenses, then make sure to add the Canon 300DG digital camera gadget bag to your list. In addition to its attractive styling, this camera bag is specifically designed with SLR cameras in mind. It's built with special compartments intended to hold up to two SLR camera bodies, three lenses, and a host of accessories. Canon has also included several padded easy-access side storage pockets so you can get at an extra memory card or lens cloth in a snap. The durable, water-repellent nylon exterior and weather-flap lid help keep the elements out, while the double-clasp closures keep your cameras safe and secure inside the bag.

- Designed to hold 1-2 SLR digital cameras
- Hold up to two SLR camera bodies, two-three lenses, and accessories
- Padded, easy-access side pockets for extra memory cards
- Durable, water-repellent nylon exterior and weather-flap lid
- Inside dimensions measure 9.5 x 7 x 6 inches (WxHxD)
- Product dimensions: 12 x 6 x 9 inches (WxHxD)
- Weight 2 lbs.